



PAINT, TAR and RUBBER REMOVER for PAVERS

{121-541 / 1 qt.}

UPDATE

November 26, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Pavers and slabs made of concrete or natural stone, masonry, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Dissolves paint, tar or bitumen, rubber and chewing gum
- Water-rinsable

DESCRIPTION

Techniseal® Paint, Tar and Rubber Remover for pavers effectively dissolves paint, tar or bitumen, rubber and chewing gum on pavers, slabs, concrete and masonry.

DIRECTIONS

BEFORE YOU BEGIN

- Wear adequate protective clothing. • **ALWAYS TEST** product on a small hidden stain to ensure the results will meet your expectations. • Surface should, ideally, be warm to the touch.

APPLICATION

Cover stain generously with Remover; let work for 5 to 10 minutes. Reapply product and, using a small nylon scrub brush, scrub until stain is dissolved. Do not let dry; rinse immediately.

NOTE: This product dissolves any sealant. Apply a new coat of sealant on stripped surface.

COVERAGE

0.7 to 1 quart per 10.75 sq. ft. The quantity required depends on the porosity of the material to be treated. It is recommended that a small area be tested to determine the exact amount needed.

STORAGE AND SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. Properly stored, the product's shelf life is 3 years following production (see date on packaging).

PACKAGING

Product Code	Retail Size	Pro Size	Units per box	Units per pallet
121-541	1 qt.	—	6	480

WARNING



DIRT & GREASE CLEANER for PAVERS

DANGER

- Flammable liquid and vapor.
- Causes serious eye irritation.
- Causes skin irritation.
- May damage the unborn child.
- Suspected of causing cancer.
- May be fatal if swallowed and enters airways.
- May cause respiratory irritation.
- May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure. (blood system) Prolonged or repeated contact may dry skin and cause irritation.

Read label before use. KEEP OUT OF THE REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 3.9%

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves: > 8 hours (breakthrough time): Recommended: butyl rubber. Wear eye or face protection: Recommended: Safety glasses. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a wellventilated area. Do not breathe vapor. Wash hands thoroughly after handling. Avoid contact with skin and clothing. Wash thoroughly after handling. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Store locked up. Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Max VOC: less than 4%

EMERGENCY PHONE: CANUTEC (613) 996-6666 / SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT

Techniseal®, 300 Liberté, Candiac (Québec), Canada J5R 6X1

SHIPPING

Land and sea: Regulated
UN 1993, class 3
Packing Group: III

LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.