



## Dirt and Grease Cleaner

for Pavers



(141-511 / 1L)

### UPDATE

#### December 8, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)  
Canada and U.S.A.: dial 1 800 465-7325  
Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

- Pavers and slabs made of concrete or natural stone
- Driveways, patios, terraces, commercial parking lots, pedestrian areas, etc.

### PROPERTIES

- Removes motor oil and grease (barbecue)
- Dissolves, dislodges and encapsulates grease
- Ideal for sealed surfaces and fresh stains\*

\*For bare surfaces and older, more stubborn stains, use Techniseal<sup>®</sup> Professional-Grade Oil & Grease Remover.

### DESCRIPTION

Techniseal<sup>®</sup> Dirt & Grease Cleaner for Pavers effectively removes motor-oil and grease stains (barbecue) from concrete pavers. Recommended for sealed surfaces and fresh stains, it dissolves, dislodges and encapsulates grease, thoroughly cleaning without leaving any oily film after rinsing.

### DIRECTIONS

#### BEFORE YOU BEGIN

- Wear rubber gloves and safety goggles. • **ALWAYS TEST** on a small hidden area to ensure that result meets your expectations.

#### APPLICATION

On a sealed surface, wet the stain before applying product; on a bare surface, apply dry. Cover the stain generously with Dirt & Grease Cleaner; let work for 2 to 3 minutes; reapply product and scrub with a Techniseal<sup>®</sup> Brush. **Do not let product dry on the surface**; rinse thoroughly. Repeat if necessary.

**IMPORTANT** : An oil spot that has penetrated the material may resurface within 24 hours following cleaning; if this occurs, lighten the stain using Techniseal® Professional-Grade Oil & Grease Remover (141-591).

## PACKAGING

Product code	Retail Size	Pro Size	Units per box	Units per pallet
141-511	1 L	—	6	480

## WARNING

**CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS.** Do not mix with Acid. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Handle with care. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection: Chemical splash goggles or face shield. Use chemical-resistant, impervious gloves. Wear appropriate respirator when ventilation is inadequate. **FIRST AID TREATMENT Contains:** Alcohols, C9-11, ethoxylated; Phosphoric acid, sodium salt, hydrate (1:3:12); disodium metasilicate; 1-propoxypropan-2-ol; Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts; (R)-p-mentha-1,8-diene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

## SHIPPING

### Land

Transported in limited quantity

### Sea

UN1760

Corrosive liquids, n.o.s. (trisodium orthophosphate, Silicic acid (H<sub>2</sub>SiO<sub>3</sub>), disodium salt, nonahydrate)

Class: 8

PG: III

## LIMITED WARRANTY

Techniseal® warrants this Dirt & Grease Cleaner against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim.