



RG+ Concrete Adhesive



(141-791 / 300 mL - 141-792 / 828 mL)

UPDATE

December 10, 2015

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com Canada and U.S.A.: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

• For pavers, slabs and retaining walls

PROPERTIES

- Premium advanced formula
- Works on wet or frozen surfaces
- Ideal for retaining walls

DESCRIPTION

TECHNISEAL RG+ CONCRETE ADHESIVE is an elastomeric resin based compound that is specially formulated for the construction of concrete hardscapes. Remaining flexible, it is ideal for the construction of retaining walls. Most effective on dry surfaces, it can also be used on wet or frozen surfaces. It provides a strong bond and resists the elements (water, frost, etc.).

DIRECTIONS

Surface should be clean and ideally dry. Apply a maximum thickness of 1 cm (3/8"); join pieces together immediately with a slight twisting motion. If surface is wet or frozen, curing will take longer. **Coverage:** A 1 cm (3/8") bead covers up to 4.5 linear meters (15 linear feet). **Cleaning of tools:** Use mineral spirits.

PACKAGING

Adhesive	Product Code	Retail Size	Units per box	Units per Pallet
RG+	141-791	300 ml	12	1296
	141-792	828 ml	12	456

WARNING

CONTENTS MAY CATCH FIRE. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not smoke. Do not get in eyes. Do not get on skin or clothing. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. **KEEP OUT OF REACH OF CHILDREN. USE ENTIRE CONTENTS ON OPENING. This container is not child-resistant once opened. FIRST AID TREATMENT Contains:** Methyl acetate. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. Calculated VOC: 7g/L

SHIPPING

Land and Sea

Transported in limited quantity

LIMITED WARRANTY

Techniseal[®] warranties this Adhesive against manufacturing defects. As Techniseal[®] has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal[®] warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice : User should make sure that this product meets their needs by carrying out a test under anticipated conditions of use. In the event that no test was carried out, the warranty won't apply.