



SLURRY REMOVER(SR) FOR PAVERS AND SLABS

UPDATE

March 27, 2014

Make sure that you have an up-to-date technical data sheet in hand by consulting our website:

techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Bare surfaces
- Concrete or clay pavers and slabs

PROPERTIES

- Removes cement slurry and polymeric sand haze

DESCRIPTION

TECHNISEAL® SR SLURRY REMOVER FOR PAVERS AND SLABS is the most effective product available for removing cement slurry and polymeric sand haze on concrete or clay pavers and slabs.

DIRECTIONS

Read the Material Safety Data Sheet before using this product. **Wear acid-resistant clothing, boots, gloves and safety goggles.**

DILUTION:

Principle: To use the strongest concentration of product without etching or discoloring pavers. A weaker concentration will increase the labor factor.

1. Into a plastic watering can, dilute 1 part product in 8 or more parts water.

2. Test the concentration on spare pavers or on a small hidden area of approximately 4 sq. ft. Test area or spare pavers must be wet.

- If the product etches or discolors the pavers: lower the concentration (1 part product in 10 parts water) until the product no longer etches or discolors the pavers.
- If the product DOES NOT etch or discolor the pavers: to increase product efficiency and reduce scrubbing, you may use a stronger concentration. The concentration must be strong enough to remove slurry without etching or discoloring pavers.

IMPORTANT:

Always test diluted product before using on the entire surface.

ALWAYS POUR THE SLURRY REMOVER INTO WATER; NEVER POUR WATER INTO THE PRODUCT.

WETTING:

To prevent product penetration and make rinsing easier, first saturate surface with water. Always work on a wet surface.

APPLICATION:

Do not use on flagstone or on natural stone.

Cement slurry on concrete pavers or slabs:

1. If application is done on pavers with new polymeric sand joints, **wait 30 days before applying the product.**
2. Using a plastic watering can, cover the cement slurry with SLURRY REMOVER. Work in small sections.
3. Lightly scrub.
4. Rinse immediately and thoroughly.

Product should not sit on the surface more than a few seconds.

Polymeric sand haze on concrete pavers or slabs:

1. If application is done on pavers with new polymeric sand joints, **wait 30 days before applying the product.**
2. Work in small sections; no more than 50 sq. ft.
3. Using a plastic watering can, cover the area with SLURRY REMOVER.
4. Lightly scrub.
5. Rinse immediately and thoroughly.
6. Move on to the next section.

Product should not sit on the surface more than a few seconds.

IMPORTANT: DO NOT let product dry on the surface. If product dries on the surface, reapply product, lightly scrub and rinse immediately and thoroughly.

TIP: To improve efficiency on large areas, 3 persons are recommended to apply the product. One person should spray (pour) the product while another is scrubbing and a third is rinsing.

COVERAGE

1 gal. of concentrated product clean up to 600 sq. ft. Coverage will depend on surface condition and product dilution.

PACKAGING

Product Code	Pro Size	Units per box	Units per pallet
221-553	1 gal.	4	144
221-556	5 gal.	-	48

WARNING**DANGER!**

CORROSIVE. CAUSES SEVERE EYE AND SKIN IRRITATION AND BURNS. MAY CAUSE IRREVERSIBLE EYE DAMAGE. INHALATION OF VAPORS OR MISTS CAUSES SEVERE IRRITATION OR BURNS OF THE NOSE, THROAT AND RESPIRATORY TRACT. MAY CAUSE LUNG DAMAGE. HARMFUL OR FATAL IF SWALLOWED.

Contains Hydrochloric Acid 7647-01-0 and Water 7732-18-5. Do not breathe vapors or mists. Prevent contact with eyes, skin and clothing. Use with only adequate ventilation. Always wear gloves, protective clothing and eye/face protection when handling this material. Wash thoroughly after handling. Keep container closed when not in use. Do not eat, drink or smoke in the work area.

FIRST AID TREATMENT: **Eye Contact:** Immediately flush eyes with water for at least 15 minutes then get immediate medical attention. **Skin Contact:** Immediately flush with water for at least 15 minutes while removing contaminated clothing and shoes. Get immediate medical attention. **Inhalation:** Move to fresh air. Support breathing if needed. Get immediate medical attention. Effects from exposure may be delayed. **Ingestion:** If conscious, rinse mouth with water and give one glass of water to drink. DOT NOT INDUCE VOMITING. Immediately call a physician or Poison Control Center. **STORAGE:** Store in cool, dry, well-ventilated area. Keep containers closed. Keep away from incompatible materials.

EMPTY CONTAINERS: Empty containers may contain product residue and may be dangerous. Do not cut, weld, drill, etc. on or near containers, even empty containers, as fire or explosion may occur. Follow all MSDS precautions in handling empty containers.

SPILL: Ventilate area. Wear appropriate protective clothing to prevent eye and skin contact including impervious

gloves and safety goggles and respirator if needed. Contain, dilute and collect using an inert, non-combustible absorbent. Place into an appropriate container for disposal. Dike large spills and collect into appropriate containers. Neutralize spill residue with dilute sodium carbonate. Prevent spill from entering waterways or sewers. Report spills and releases as required to appropriate authorities.

BASIC FIREFIGHTING PROCEDURES: Use any media that is appropriate for the surrounding fire. Firefighters should always wear positive pressure self-contained breathing apparatus and protective clothing when fighting fires involving chemicals. Follow all MSDS precautions in firefighting procedures.

FOR PROFESSIONAL USE ONLY.

FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET.

SHIPPING

Land and sea

Hydrochloric acid in solution

Class: 8

UN Number: 1789

Packing Group: II

Flash Point: n/a

LIMITED WARRANTY

LIMITED WARRANTY: Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.